

## **NON-STRUCTURAL GRIPDECK FORMPLY**

## **PRODUCT SPECIFICATIONS**

Product:	NON-STRUCTURAL GRIPDECK NON-SLIP FORMPLY
Veneer Grade:	Resin-impregnated Phenolic Film
Core Timber Species:	(Eucalyptus, Hardwood)
	(Populus, Hardwood)
Standard:	EN314-2
Sheet Size:	2440 x 1220mm
Thicknesses:	12mm, 18mm
Density:	580-610kgs/m <sup>3</sup> (approx.)
Glue Bond:	Type "B" Bond
Formaldehyde:	Emission "E1"
Applications:	General purpose construction, manufacturing, DIY, etc.

## **PRODUCT DESCRIPTION**

A hardwood plywood with a hard-wearing black overlay surface embossed slip-resistant face & smooth back with acrylic painted edges. It is fit for use in applications that require a durable finish and moisture resistance subject to limited exposure. Non-structural products must not be used in any structural or load-bearing applications.

Please ensure any cut edges are resealed.

## Disclaimer

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with Luxon or not. This information cannot be warranted by Luxon to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances.

C:\OneDrive\01 Plywood Documents\Specification Sheets Version 15-02-2023 11:00 www.luxon.com.au Luxon Pty Ltd 23 Sudbury Street, Darra QLD 4076 PO Box 3093, Newstead QLD 4006